


## SILICON POWER SWITCHING TRANSISTORS



2N5320, 2N5321 NPN  
2N5322, 2N5323 PNP

TO-39  
Metal Can Package

### Medium Power Amplifier and Switching Applications

#### ABSOLUTE MAXIMUM RATINGS


DESCRIPTION	SYMBOL	2N5320	2N5321	2N5322	2N5323	UNITS
Collector Emitter Voltage	$V_{CEO}$	75	50	75	50	V
Collector Base Voltage	$V_{CBO}$	100	75	100	75	V
Emitter Base Voltage	$V_{EBO}$	7	5	7	5	V
Collector Current - Continuous	$I_C$	2.0				A
Base Current	$I_B$	1.0				A
Power Dissipation@ $T_a=25^\circ\text{C}$ Derate Above $25^\circ\text{C}$	$P_D$	1 5.71				W mW/ $^\circ\text{C}$
Power Dissipation@ $T_c=25^\circ\text{C}$ Derate Above $25^\circ\text{C}$	$P_D$	10 57.14				W mW/ $^\circ\text{C}$
Operating And Storage Junction Temperature Range	$T_j, T_{stg}$	- 65 to +200				$^\circ\text{C}$

#### THERMAL CHARACTERISTICS

Junction to Ambient in free air	$R_{th(j-a)}$	175	$^\circ\text{C/W}$
Junction to Case	$R_{th(j-c)}$	17.5	$^\circ\text{C/W}$

#### ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$ unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Collector Emitter Voltage	$V_{CEO}$	$I_C=100\text{mA}, I_B=0$ <b>2N5320/5322</b> <b>2N5321/5323</b>	75 50		V V
Collector Cut Off Current	$I_{CEX}$	$V_{CE}=70\text{V}, V_{BE}=1.5\text{V}, T_c=150^\circ\text{C}$ <b>2N5320/5322</b>		5	mA
		$V_{CE}=45\text{V}, V_{BE}=1.5\text{V}, T_c=150^\circ\text{C}$ <b>2N5321/5323</b>		5	mA
		$V_{CE}=100\text{V}, V_{BE}=1.5\text{V}$ <b>2N5320/5322</b>		100	$\mu\text{A}$
		$V_{CE}=75\text{V}, V_{BE}=1.5\text{V}$ <b>2N5321/5323</b>		100	$\mu\text{A}$
Emitter Cut Off Current	$I_{EBO}$	$V_{BE}=5\text{V}, I_C=0$ <b>2N5321/5323</b>		100	$\mu\text{A}$
		$V_{BE}=7\text{V}, I_C=0$ <b>2N5320/5322</b>		100	$\mu\text{A}$



TO-39  
Metal Can Package

ELECTRICAL CHARACTERISTICS (T<sub>a</sub>=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNITS
DC Current Gain	$*h_{FE}$	$I_C=1A, V_{CE}=2V$ <b>2N5320/5322</b>	10			
		$I_C=0.5A, V_{CE}=4V$ <b>2N5320/5322</b> <b>2N5321/5323</b>	30 40		130 250	
Collector Emitter Saturation Voltage	$*V_{CE(sat)}$	$I_C=500mA, I_B=50mA$ <b>2N5320</b> <b>2N5321</b> <b>2N5322</b> <b>2N5323</b>			0.5 0.8 0.7 1.2	V V V V
Base Emitter On Voltage	$*V_{BE(on)}$	$I_C=500mA, V_{CE}=4V$ <b>2N5320/5322</b> <b>2N5321/5323</b>			1.1 1.4	V V

DYNAMIC CHARACTERISTICS

Small Signal Current Gain	$h_{fe}$	$I_C=50mA, V_{CE}=4V, f=10MHz$	5			
---------------------------	----------	--------------------------------	---	--	--	--


SWITCHING CHARACTERISTICS

Turn On time	$t_{on}$	$V_{CC}=30V, I_C=500mA, I_{B1}=50mA$ <b>2N5320/5321</b> <b>2N5322/5323</b>			80 100	ns ns
Turn Off time	$t_{off}$	$V_{CC}=30V, I_C=500mA, I_{B1}=I_{B2}=50mA$ <b>2N5320/5321</b> <b>2N5322/5323</b>			800 1000	ns ns

\*Pulsed: Pulse width  $\leq 300ms$ , duty cycle  $\leq 2\%$


TO-39  
Metal Can Package

TO-39 Metal Can Package



All dimensions are in mm

DIM	MIN	MAX
A	8.50	9.39
B	7.74	8.50
C	6.09	6.60
D	0.40	0.53
E	—	0.88
F	2.41	2.66
G	4.82	5.33
H	0.71	0.86
J	0.73	1.02
K	12.70	—
L	42 DEG	48 DEG



PIN CONFIGURATION  
1. EMITTER  
2. BASE  
3. COLLECTOR

Packing Details

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-39	500 pcs/polybag	540 gm/500 pcs	3" x 7.5" x 7.5"	20K	17" x 15" x 13.5"	32K	40 kgs

**Disclaimer**

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
**Continental Device India Limited**

C-120 Naraina Industrial Area, New Delhi 110 028, India.  
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119  
email@cdil.com www.cdilsemi.com