





型号说明 Ordering Information




技术特性 Specification

- 规格 Rating: () 10A 125/250VAC
(A) 16A 125/250VAC
(B) 5A 125/250VAC
- 接触电阻 Contact Resistance: 20mΩ max
- 绝缘电阻 Insulation Resistance: 500VDC 100MΩ min
- 耐电压 Dielectric Strength: 1500VAC, 1Minute
- 环境温度 Ambient Temperature: -25°C ~ +85°C
- 电气寿命 Electrical Life: 100,000 Cycles

电路特性 Circuitry trait



端子种类 Terminal options



操作力 Operating force

L : 35g±15g
 S: 160g±40g
 H: 320g±80g

	<p>MSW-01 ON-(ON) 10A 125/250VAC MSW-01A ON-(ON) 16A 125/250VAC SPDT 3P</p>		
	<p>MSW-02 ON-(ON) 10A 125/250VAC MSW-02A ON-(ON) 16A 125/250VAC SPDT 3P L=13; 27; 38; 53</p>		
	<p>MSW-03 ON-(ON) 10A 125/250VAC MSW-03A ON-(ON) 16A 125/250VAC SPDT 3P L=12; 25</p>		
	<p>MSW-04 ON-(ON) 10A 125/250VAC MSW-04A ON-(ON) 16A 125/250VAC SPDT 3P</p>		